


**Electrical data:**

**Impedance:** 50 ohm  
**Frequency range:** DC to 6 GHz  
**VSWR:** ≤1.25, DC-6.0 GHz  
**Insulation resistance:** ≥5000 MΩ  
**Test voltage:** 2500 V(vrms)  
**Working voltage:** 1400 V(vrms)  
**Contact resistance:**  
 1). Centre contact: 1.0 mΩ  
 2). Outer conductor: 0.2 mΩ  
**Average Power:** 5.0 W



5	1	O-ring	Silicone rubber	
4	1	Coupling nut	Brass/Nickel plated	Nickel 7.0um over Copper 2.0um
3	1	Body	Brass/Nickel plated	Nickel 7.0um over Copper 2.0um
2	1	Insulation	PTFE	
1	1	Centre contact	Brass/Gold plated	Gold 0.3um over Nickel 2.0um
Itemref	Quantity	Title/Name, designation, material, dimension etc		Article No./Reference

Designed by Mingang Han	Checked by Jinlong Gu	Approved by - date Hongyu Du	File name N-JR-5.0	Date 08.04.20	Scale 1:1
Amitron Electronics, Ltd.			N-JR-5.0		
			<a href="http://www.amel.ru">http://www.amel.ru</a>	1.0	1/1