




DRAWING



CABLE (PK50-3-38, LMR200)

CRIMPED FERRULE HEX CRIMP SIZE



6	1	Crimp ferrule	Copper alloy/Nickel plated	Nickel 5.0um over Copper 2.0um
5	1	O ring	Silicon rubber	
4	1	Coupling nut	Brass/Nickel plated	Nickel 5.0um over Copper 2.0um
3	1	Body	Brass/Nickel plated	Nickel 5.0um over Copper 2.0um
2	1	Insulator	PFTE	
1	1	Center contact	Brass/Gold plated	Gold 0.5um over Nickel 2.0um
Itemref	Quantity	Title/Name, designation, material, dimension etc		Article No./Reference

Designed by

Checked by

Approved by - date

File name

Date

Scale

Amitron Electronics, Ltd.

SMA-JW200L

<http://www.amel.ru>

Edition

Sheet

CHARACTERISTICS

DESCRIPTION:	SMA Type male R/A connector
--------------	-----------------------------

Electrical data:

<i>Impedance:</i>	<i>50 ohm</i>
<i>Frequency range:</i>	<i>DC to 12.4 GHz</i>
<i>VSWR:</i>	$\leq 1.15 + 0.02 \times f \text{ [GHz]}, \text{ DC to 6 GHz}$
<i>Insertion loss:</i>	$\leq 0.15 \times \sqrt{f \text{ [GHz]}} \text{ dB}$
<i>Insulation resistance:</i>	$\geq 5000 \text{ M}\Omega$
<i>Test voltage:</i>	<i>1000 V rms</i>
<i>Working voltage:</i>	<i>480 V rms</i>
<i>Contact resistance:</i>	
1). <i>Centre contact:</i>	<i>3.0 mΩ</i>
2). <i>Outer conductor:</i>	<i>2.0 mΩ</i>
<i>Power handling (at 20 °C, sea level, VSWR 1.0)</i>	$\leq 200 \text{ W @ 2 GHz};$
<i>RF-leakage</i>	$\geq 100 \text{ dB up to 1 GHz}$

- Limitations are possible due to the used cable type -

Environmental data:

<i>Temperature rating:</i>	<i>-65 ° C to 165 ° C</i>
<i>2002/95/EC (RoHS):</i>	<i>Compliant</i>

Mechanical data:

<i>Mating cycles:</i>	≥ 500
<i>Coupling nut retention</i>	$\geq 270 \text{ N}$
<i>Coupling test torque:</i>	$\leq 1.7 \text{ Nm}$
<i>Recommended torque:</i>	<i>0.46 Nm to 0.69 Nm</i>

Suitable cables:

LMR200
PK50-3-38

Amitron Electronics, Ltd.

<http://www.amel.ru>

e-mail: mailbox@amel.ru