


## Coaxial Straight Flange Connector: SMB-JFD5

### Description

Straight panel receptacle jack (male), flange mount

### Interface standards

MIL-C-39012



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	4 GHz
VSWR	1.05+0.03 $\times$ f(GHz) max
Voltage rating	250 V(rms)
Test voltage	750 V(rms)
Contact resistance:	
Center conductor	$\leq$ 6m $\Omega$
Out conductor	$\leq$ 1.5m $\Omega$
Insulation resistance	$\geq$ 1000M $\Omega$

#### Mechanical Data

Weight	2.6 g
Durability	500 Cycles

#### Environmental Data

Operating Temperature	-65 $^{\circ}$ C to 165 $^{\circ}$ C
-----------------------	--------------------------------------

#### Material Data

##### Piece Parts


Piece Parts	Material
Body	Brass
Center contact	Brass
Insulator	PTFE

##### Surface Plating( $\mu$ m)

Gold 0.2 over Nickel 2.0
Gold 0.5 over Nickel 2.0

# Coaxial Straight Flange Connector: SMB-JFD5

## Outline drawing



## Packaging

Standard

Other

150/Box=15 Bag

Contact us